

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS


IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)



Europäisches Patentamt
European Patent Office
Office européen des brevets



BD

(11) EP 0 902 582 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.03.1999 Bulletin 1999/11

(51) Int Cl.6: H04N 1/00

(21) Application number: 98307359.4

(22) Date of filing: 11.09.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

• Barrett, Michael W.
Fairport, New York 14450 (US)
• Martin, Andrew T.
Webster, New York 14580 (US)

(30) Priority: 15.09.1997 US 929519

(71) Applicant XEROX CORPORATION
Rochester, New York 14644 (US)

(74) Representative:
Skone James, Robert Edmund et al
GILL JENNINGS & EVERY
Broadgate House
7 Eldon Street
London EC2M 7LH (GB)

(72) Inventors
• Knodt, Ruediger W.
Rochester, New York 14618 (US)

(54) User interface with immediate indicators of concurrence, in use, available, and not available features

(57) A method of providing immediate status and capability indicators of an imaging device (2) to an operator by displaying at the user interface display screen (40) an indicator of imaging device features available for operation and a display of imaging device features not available for operation. There is also provided a display

of imaging device features in use by animating the display screen and there are displayed connecting channels indicating connection of the imaging device to other devices on the network. Finally, there is presented to the operator a manifestation of the capability of concurrent feature operation of the imaging device.




FIG. 1

78

Description

[0001] The present invention relates to a user interface, in particular, to a technique of immediate presentation to an operator of the concurrence capability of features in a machine as well as immediate presentation of those features in use, available, and not available for a given machine.

[0002] To meet modern document needs, document systems have been provided with ever expanding feature sets for various local and remote applications such as document copy, document distribution, document storage, and document printing. In the past, to expand feature sets, existing control panels were usually augmented with more menu layers, an increased number of categories of features, and increased numbers of buttons and icons. As a result, end user operators are often confronted with a control panel search task in order to locate and access the particular set of features and electronic dialogs needed for a particular job.

[0003] This has only aggravated job set up complexity for operators. The problem is further intensified when multifunctional features such as fax, print, store, and distribute are required. In these situations, users and operators are often confused on the availability of features and proper selection and combination of features to achieve a given job objective.

[0004] U.S. Pat. No. 5,450,571, assigned to the same assignee as the present invention, discloses a dialog filtering process for a printing system to filter out non-selectable print programming selections. U.S. Pat. No. 5,513,126, assigned to the same assignee as the present invention, discloses a network having selectively accessible recipient prioritized communication channel profiles. In particular, a sender can automatically distribute information to a receiver on a network using devices and communication channels defined in a receiver profile. In addition, U.S. Serial No. 08/329,811 (D/94101) filed October 27, 1994 discloses a method of customizing and storing an interface control for a machine by entering an interface control customizing mode. This provides access to a library of control features for selecting a set of control features for use on a given machine and for arranging the set of control features in a given configuration on a scaled representation of an interface control. The set of control features and given configuration are referenced with a given identifier whereby upon accessing the identifier the set of control features and given configuration are provided on the interface control display. U.S. Serial No. 08/541,547 (D/95418) filed October 10, 1995 discloses a method a using customized interface control panels.

[0005] A difficulty with the aforementioned systems, however, is that they are relatively complicated. For example, U.S. Pat. No. 5,450,571, deals with print queues and providing common electronic job tickets with inter-client protocol and client-server protocol formats including providing printer user interface mask files for each

printer. Or they deal with set up, storing and retrieving of customized control panels as disclosed in U.S. Pat. No. 5,513,126 are concerned with communication channel profiles for sending and receiving information over a network.

[0006] A further difficulty is that prior art systems do not account for and simplify for the operator the high degree of automation, networking, interdependency, remote operation, concurrency, faxing, scanning, printing, and traditional copier functionality of existing machines. It would be desirable, therefore, to present to the user an immediate indication of the status and capability of a given machine. That is, it would be desirable to give the operator an immediate and easily recognizable indication of the ability of the machine for concurrent operation of features as well as the current use and capability of network connection.

[0007] It is an object of the present invention, therefore, to provide a new and improved user interface that mimics machine activities as the activities occur and provides timing information, functional sequences, and capabilities of a given machine in its network environment. It is still another object of the present invention to immediately present to an operator the concurrence capability of features in a machine as well as immediate presentation of those features in use, available, and not available for a given machine. Other advantages of the present invention will become apparent as the following description proceeds, and the features characterizing the invention will be pointed out with particularity in the claims annexed to and forming a part of this specification.

[0008] The present invention is concerned with a method of providing immediate status and capability indicators of an imaging device to an operator by displaying at the user interface display screen an indicator of imaging device features available for operation as well as a display of imaging device features not available for operation. There is also provided a display of imaging device features in use by animating the display screen and there are displayed connecting channels indicating connection of the imaging device to other devices on the network. Finally, there is presented to the operator a manifestation of the capability of concurrent feature operation of the imaging device.

[0009] For a better understanding of the present invention, reference may be made to the accompanying drawings wherein the same reference numerals have been applied to like parts and wherein:-

Figure 1 is an illustration of a system environment incorporating the present invention;

Figures 2, 3 and 4 are representations of various screen displays portrayed to an operator in accordance with the present invention;

Figures 5-9 illustrate a display of a copier job in progress in accordance with the present invention; Figure 10-13 illustrate a printing job in progress in

accordance with the present invention; and, Figure 14 is a flow chart illustrating the immediate presentation to an operator of the concurrence capability of features in a machine as well as immediate presentation of those features in use, available, and not available for a given machine in accordance with the present invention.

[0010] While the present invention will hereinafter be described in connection with a preferred embodiment thereof, it will be understood that it is not intended to limit the invention to that embodiment. On the contrary, it is intended to cover all alternatives, modifications, and equivalents, as may be included within the spirit and scope of the invention.

[0011] Referring now to the drawings and in particular to Figure 1, an exemplary multimedia device information system or network 2 including work station 4, enables users to communicate in a transparent and device independent manner. Multimedia system 2 can be implemented using a variety of hardware platforms and includes devices for input including scanner or digital copier 5, keyboard 6, pointing device or mouse 7, microphone 8, and video camera 9.

[0012] The system further has devices for output including display terminal 10, printer 11, and speakers 12. Input/output (I/O) devices include facsimile 13, file server 14, and telephone 15. Server 14 is configured central to or remote from work station 4 with public, shared and/or private data storage that is differentiated by user access rights. The server 14 includes relational database system 17, network administration system 18, mail system 19 (e.g. e-mail, voice mail) and data storage and retrieval system 20, and can be physically configured using optical drives, hard drives, floppy drives and/or tape drives. The relational database system 17 provides systems with fast query and retrieval of data.

[0013] Work station 4 operates in a collaborative environment, where users at different Work stations 4 can work together in real time to process and distribute public, shared or private information existing in different forms. (Public data is defined herein as data accessible by anyone, shared data is defined as data accessible by a limited number of users and private data is data uniquely accessible by a single user.) Work station 4 can exist in a distributed or centralized environment. In either environment Work station 4 is connected to other systems and devices through local area network (LAN) 24, gateway 25, and/or modem 26. In distributed systems, a number of Work stations extend distributed processing and storage capabilities to each other, by providing for example redundant storage or a single mounting of a unique application.

[0014] Work station 4 includes an object oriented user interface (UI) 40 that uses icons and windows to represent various data objects and user applications such as a display illustrating an office desktop metaphor employing various abstractions of a typical office environment.

User interfaces using windows and icons having an object oriented methodology to present metaphors for maintaining data, navigating through various user spaces and presenting abstract computer concepts are well known.

[0015] This example of the invention consists of a small icon like machine mimic with radiating activity vectors or branches. The small machine icon is centrally positioned relative to its feature extension. This puts emphasis where it should be and illustrates the multifaceted, multi tasking, and concurrent activities the system engages in. It also relieves any contention problem by showing system job entry points, times, and feature priorities, e.g. scanning is available while printing.

[0016] The model is a metaphor for various products increasing learning-comprehension, and serves as an archetypal logo for related systems graphics, icons, instructional material, and systems collateral. It is a model graphic suitable for a "Touch Me" introductory frame, tutoring the novice user. Programmed Copy-, Scan-, and Fax Out Jobs display anticipated completion time, advising the user when to pick up a job. It provides a walk-up user with information when a job is going to start. The model is visually related to network diagrams, printed circuit boards, and electronic chip design.

[0017] This model could be used as a Tutorial Walk-Up screen that would be dynamic in nature, but not necessarily functional. Another alternative is a model that is very functional, showing the system in totality, that makes useful comments on what is currently happening, what is going to happen, and where access points are to get your job done, e.g. scanning while printing. The model also could highlight paper trays being used, their status, etc.

[0018] A dynamic display in accordance with the present invention provides immediate status and capability indicators of an imaging device. The indicators include visual prompts to an operator of imaging device features available for operation and of imaging device features not available for operation. The use of animation provides a prompt of device features already in use or operation. Shown, are connecting channels between displayed devices suggesting network connections and capability. In addition, presented to the operator is a manifestation of the capability of concurrent feature operation of the imaging device. That is, those device features that can be operated concurrently are prompted to the operator by a visual dynamic.

[0019] With reference to Figures 2, 3 and 4, there is illustrated a dynamic tutorial of machine status. As shown, there is an imaging device representation 50 which generally indicates the devices to which the work station 4 is attached to via the LAN 24. This may therefore represent a single imaging device (not shown) capable of performing many functions or alternatively it may represent a number of devices such as the printer 11, the scanner 5, the facsimile 13, or the like. The imaging device representation 50 will hereinafter be re-

ferred to simply as the device 50 whether it represents single or multiple devices.

[0020] In this example, the device 50 is interconnected to a copy job status indicator 52, a print job status indicator 54 and fax in job indicator 56A via a web of interconnections or network 57. Similarly, a files status indicator 58, device indicator 60, and fax out job indicator 56B are shown connected to the device 50 by a web configuration or a network 61.

[0021] The darkened connection 57A of the web 57 indicates a current operation of the device 50 in the copy job mode. A not shown phantom designation of a connector would however indicate the respective function as not being currently available on device 50. The document designations 53 and 55 illustrate the movement of documents to the device 50, as will be explained in more detail below.

[0022] Figure 2 illustrates an activity diagram whilst Figure 3 illustrates the status of device 50 in more detail. In particular, document representations 62 illustrate a set of documents to be copied while box 65 illustrates two minutes for a job completion. As the job nears completion, selected documents 62 will be illustrated as traversing the connection 57A toward the device 50 as will be explained below. When the job progresses, the time to completion illustrated will be commensurate with the percentage of documents that have accumulated at the device 50. Similarly, there is a fax out display at 68 to illustrate the time to completion of a fax job being sent out from device 50 if the device includes such a feature.

[0023] In Figure 4, channel or web segment 74 can be lightened or faded to indicate "not in use" and the channel 72 is highlighted or darkened to illustrate that a print job is now in process. Also the web or channel 76 can be highlighted or shaded to indicate that a scan to file is taking place and that it is taking place concurrently with the print job operation. The display 70 illustrates the time to completion of the scan to file portion of the job. It should be noted that it is merely a design choice to use any form of shading, highlighting, cross hatching, phantom display, or any other screen technique to illustrate machine states. These states include various features and options such as feature availability, current feature use, the capability of concurrent use of features, the unavailability of features, and progressive or animated display.

[0024] The sequence of the copy job operation is further illustrated with reference to Figures 5-9. In this case, the connections 61B and 57B which indicate the Fax In and Fax Out features are shown in phantom, indicating these functions are not available on this given machine.

[0025] It will also be noted that an additional feature indicator 79 indicates that the fax feature is not currently available.

[0026] Figure 5 shows the initial situation in which there are a number of document representations 62 positioned near the copy job status indicator 52, indicating

that there are currently a set of documents to be copied. The box 65 includes a number "2" indicating that the set of documents will take two minutes to copy. There are also (Figure 6) a set of document representations 78 adjacent the print jobs indicator 54 indicating a number of documents in a print queue. In this case, however, the connection 57a is darkened indicating copying is currently occurring, whilst connection 57c is lightened indicating that printing will occur in due course.

[0027] As shown in Figure 6, respective document representations 62a, 62b, 62c, 62d of the set of document representations 62 traverse the connection 57a towards the device 50 indicating that copying is in progress.

[0028] As copying progresses, as shown in Figure 7, the number of document representations on the connection 57a will decrease in proportion to the amount of copying completed. Thus, as shown, document representation 62a has disappeared whilst document representations 62b, 62c and 62d have moved along the connection 57a towards the device 50. Furthermore, the time indication in the box 65 has also been reduced indicating the amount of time left for copying to be completed. This procedure continues in Figure 8 with further document representations 62 being transferred to the device 50.

The number in the box 65 is also further reduced.

[0029] Finally, in Figure 9, the copy job is completed and all the document representations 62 have now been removed from the connection 57a and a "0" is included in the box 65 indicating that the copy job is completed.

[0030] With the copy job completed, it is now possible for the device 50 to commence with the printing job, as shown in Figure 10. Accordingly, the connection 57c, that being the connection related to printing jobs is darkened indicating that printing is occurring.

[0031] As shown in Figure 11, as printing commences, various document representations 78a, 78b, 78c move along the connection 57c towards the device 50. This indicates that printing is in progress.

[0032] As shown in Figure 12, as printing continues, the document representations 78a and 78b will reach the device 50 and be removed from the connection 57c. Subsequent document representations 78c, 78d, 78e move further along the connection 57c indicating the proportion of the printing job that has been completed. Finally, as shown in Figure 13, the print job is completed and all the document representations in the set of document representations 78 have moved along the connection 57c to the device 50.

[0033] It should be understood that this is an animated display and along with the alternate shading of the connecting webs or network stated above, enables the operator to immediately observe and determine the current operation of the machine, the features that are available or are not available on the machine, the capability for concurrent operation of selected features, as well as the degree of completion of the various selected features.

[0034] These features are illustrated with reference to the flow chart of Figure 14. In particular, the various fea-

tures are scanned as shown in block 80 to determine the status of the device, as shown in block 82. In order to achieve the scanning process, it is necessary for the respective work station 4 to generate a polling signal requesting status information. This will be transferred via the LAN 24 to each respective device shown. Each device will then generate a signal indicating the current device status which will be returned via the LAN 24 to the respective work station 4. The work station 4 decodes the signals to determine the device status.

[0035] It will however be realised that each device may be configured to automatically generate status signals, thereby allowing each work station 4, connected to the LAN 24, to determine the respective status of each device at any particular time. For each device, if the device is not in use, then the feature is blocked out of the screen display as illustrated at 84. If the device is in use, then, as illustrated in block 86, a decision is made as to whether or not it is part of a network connection. If not, the portion of the display illustrating a network connection is faded or eliminated as shown in block 88. If there is a network connection, as shown in block 90, the connection is highlighted on the display.

[0036] Next there is a determination whether or not selected features such as features 1 or 2 are in use as shown in block 92. These typically are features such as a copy jobs operation or print jobs operation where animation on the screen is appropriate to illustrate the concurrency and nearness of completion of the job. If there are such features, as shown in block 94, these features are highlighted on the display with animation. If no such features, then there is a determination if other features are in use as illustrated in decision block 96. If "yes", then these features are highlighted on the display as shown in block 98. Even if there are no such features there must be a determination whether or not concurrent operation is available as illustrated at block 100. If concurrent operation is available or possible on a given machine, then the display is illuminated or back dropped to suitably display concurrency as shown in block 102. If not, the scanning and displaying is complete and the scan operation is exited as shown in block 104.

Claims

1. A method of providing immediate status indicators of an imaging device to an operator, the imaging device including a user interface with display screen providing a plurality of feature selections, the method comprising the steps of:

providing at the user interface display screen a display of imaging device features in use,
showing connecting channels on the display screen indicating connection of the imaging device to other devices on the network, and
and displaying at the user interface an indicator

of imaging device features available for operation.

2. A method according to claim 1, further comprising displaying at the user interface display screen an indicator of imaging system features available for operation.
3. The method of claim 1 or claim 2, including the step of presenting to the operator a display of the capability of concurrent feature operation of the imaging device.
4. The method of claim 3, wherein the step of presenting to the operator a manifestation of the capability of concurrent feature operation of the imaging system includes the step of visually linking indicators of features capable of concurrent operation.
5. A method according to claim 3 or claim 4, wherein the features capable of concurrent operation are printing and scanning operations or printing and facsimile operations.
6. The method of any of the preceding claims, including the step of providing a display of features not available to the imaging system.
7. The method of any of the preceding claims, wherein the step of providing at the user interface display screen a display of imaging system features in use includes the step of animating the display screen.
8. The method of any of the preceding claims, wherein the imaging system is connected to a network and the display includes a connecting channel indicating connection of devices on the network.
9. The method of any of the preceding claims, wherein the step of providing at the user interface display screen a display of imaging system features in use includes the step of animating the display screen.
10. The method of claim 9, wherein the devices include printers and facsimile devices.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13

FIG. 14



THIS PAGE BLANK (USPTO)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 902 582 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
19.01.2000 Bulletin 2000/03

(51) Int Cl.7: H04N 1/00

(43) Date of publication A2:
17.03.1999 Bulletin 1999/11

(21) Application number: 98307359.4

(22) Date of filing: 11.09.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

- Barrett, Michael W.
Fairport, New York 14450 (US)
- Martin, Andrew T.
Webster, New York 14580 (US)

(30) Priority: 15.09.1997 US 929519

(71) Applicant: XEROX CORPORATION
Rochester, New York 14644 (US)

(74) Representative:
Skone James, Robert Edmund et al
GILL JENNINGS & EVERY
Broadgate House
7 Eldon Street
London EC2M 7LH (GB)

(72) Inventors:
• Knodt, Ruediger W.
Rochester, New York 14618 (US)

(54) User interface with immediate indicators of concurrence, in use, available, and not available features

(57) A method of providing immediate status and capability indicators of an imaging device (2) to an operator by displaying at the user interface display screen (40) an indicator of imaging device features available for operation and a display of imaging device features not available for operation. There is also provided a display

of imaging device features in use by animating the display screen and there are displayed connecting channels indicating connection of the imaging device to other devices on the network. Finally, there is presented to the operator a manifestation of the capability of concurrent feature operation of the imaging device.




FIG. 1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 7359

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
Y	EP 0 679 014 A (CANON KK) 25 October 1995 (1995-10-25) * the whole document *	1,2,8	H04N1/00
Y	US 5 548 722 A (BINGHAM CHRISTOPHER R ET AL) 20 August 1996 (1996-08-20) * column 17, line 24 - column 18, line 47; figure 7 *	1,2,8	
A	DE 195 17 961 A (RICOH KK) 7 December 1995 (1995-12-07) * claims 1-3; figure 4 *	3	
A	EP 0 778 692 A (TOKYO SHIBAURA ELECTRIC CO) 11 June 1997 (1997-06-11)	3	
A	US 5 493 408 A (HIKAWA YUJI ET AL) 20 February 1996 (1996-02-20) * abstract; figures 5B,10 *		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04N G06F
Place of search		Date of completion of the search	Examiner
THE HAGUE		26 November 1999	Hanratty, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 30 7359

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-11-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0679014 A	25-10-1995	CN 1120772 A JP 8006884 A US 5935217 A	17-04-1996 12-01-1996 10-08-1999
US 5548722 A	20-08-1996	NONE	
DE 19517961 A	07-12-1995	JP 7311729 A US 5809301 A	28-11-1995 15-09-1998
EP 0778692 A	11-06-1997	JP 9163061 A CN 1166659 A	20-06-1997 03-12-1997
US 5493408 A	20-02-1996	JP 2773519 B JP 5241746 A	09-07-1998 21-09-1993

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)